

**图示(Pic. shown) : TLPS-006V-06P-G12**


General.	PCB Connector Rated : 160V,5A , 0.75mm <sup>2</sup>
	Single row , 2.50mm pitch , 02-24 Pole
	Wiring orientation: 180°(wire to plug-in )
	Spring clamp unit.

认证 ( Approval ) :



技术参数 Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	150V	--	--	--	160V	--
额定电流(Rated current)	5A	--	--	--	5A	--
额定连接容量(Rated connection capacity)	28-20AWG Sol&Str			0.25-0.75mm <sup>2</sup>		
绝缘材料(Insulation Material)				PA66 UL94 V-0		
电流承载部件材料和镀层( Material & Plating of Current carrier )				Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring )				--		
绝缘电阻(Insulation Resistance)				500MΩ or more at DC500V		
耐电压(1分钟)(Withstanding Voltage/1Min)						
额定冲击电压(Rated surge voltage)				--		
接线螺丝(Wire clamp unit Screw) , 最大扭矩( torque Max. )				--		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				8.0mm		
使用温度(Operating temperature)				-40°C up to +105°C		
焊接方式(Soldering recommend)				--		

**订购方式(How to order)**



Web:www.china-tianli.com TEL:+86-574-6347-9600,6389-6436 Mail : sale@china-tianli.cn  
地址:中国浙江省宁波杭州湾新区庵东工业园区纬三路138号  
ADD : 138 , Weisan Rd.,Andong Development Zone, Hangzhou Bay Area, Ningbo, Zhejiang, China

■ 针座 ( Pin header ) — single row



P/N : TLPHC-006V  
Orientation :  
90° ( plug-in to board )  
Rated:150V,5A  
Closed side



P/N : TLPHC-006R  
Orientation :  
180° ( plug-in to board )  
Rated:150V,5A  
Closed side