





PCB Connector — TLP series (Pinheader)— TLPHW-313R




■ 图示(Pic. shown) : TLPHW-313R-05P-G12

General:
PCB Connector Rated : 400V,13A
Single row , 5.08mm pitch , 02-24 Pole
Orientation:180°(plug-in to board)

认证 (Approval) :   

技术参数 Technical Data	UL standard			IEC standard		
	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	250V	320V	400V
额定电流(Rated current)	13A	--	10A	13A	13A	13A
额定连接容量(Rated connection capacity)	--			--		
绝缘材料(Insulation Material)	PBT UL94 V-0					
绝缘材料组别(Material group)	IIla					
电流承载部件材料和镀层(Material & Plating of Current carrier)	Copper alloy , Tin plated					
接线弹片材料(Material of Clamp spring)	--					
耐电压(1分钟)(Withstanding Voltage/1Min)	1600V					
额定冲击电压(Rated surge voltage)	4000V					
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)	--					
固定螺丝(Mounting Screw) , 扭矩(torque)	M2.5, 0.2 ~ 0.25N·m					
剥线长度(Wire stripping length)	--					
使用温度(Operating temperature)	-40°C up to +120°C(UL) / -40°C up to +115°C(IEC)					
存储温度(Storage temperature)	-40°C up to +70°C					
存储相对湿度(Storage relative humidity)	≤70%					
焊接方式(Soldering recommend)	Wave soldering ,260°C 8S Max					

■ 订购方式(How to order)



Web:www.tielee.com TEL:+86-574-6347-9600,6389-6436 Mail : sale@china-tianli.cn
地址:中国浙江省宁波杭州湾新区庵东工业园区纬三路138号
ADD : 138 , Weisan Rd.,Andong Development Zone, Hangzhou Bay Area, Ningbo, Zhejiang, China

■ 编码片 Coding key



P/N:
TLPCK-001-S

■ 插头 (Female Connector) — single row



P/N : TLPSW-313V
Wiring orientation :
180°(wire to plug-in)
Rated : 630V,13A , 1.5mm²
Screw clamp unit: M2 , 0.2N·m