



M5-公头注塑成型式-屏蔽 弯头 A-coding

M5 Male Overmolded with Cable plug Shielded, Angled, A-coding



技术参数 Technical Specifications

芯数 Numer of Pin	3	4
认证Certification		
Pin分布图 (公头)		
接触阻抗Contact impedance	$\leq 5m\Omega$	
绝缘阻抗Insulation resistance	$\geq 100M\Omega$	
插拔次数Number of plug and unplug cycles	≥ 100	
环境温度Ambient temperature	$-25^{\circ}C \sim 80^{\circ}C$	
防护等级Ingress protection	IP67	
胶芯材质Rubber core material	PA	
端子材料Terminal material	铜镀金 copper alloy Gold-plated	
是否屏蔽Shielding	屏蔽 Shielded	
执行标准Enforce the standard	IEC 61076-2-105	
额定电压Rated voltage	60V	
额定电流rated current	1A	
导体规格Conductor specifications	0.14mm ² /26AWG	

产品料号 Product Part Number

芯数 Numer of Pin	线缆长度length (M)	公头	
		PVC (订购方式 How to order)	PUR (订购方式 How to order)
3	1	TCC-105MR-AH012-03P-C1.0-000	TCC-105MR-AH012-03P-R1.0-000
	3	TCC-105MR-AH012-03P-C3.0-000	TCC-105MR-AH012-03P-R3.0-000
	5	TCC-105MR-AH012-03P-C5.0-000	TCC-105MR-AH012-03P-R5.0-000
4	1	TCC-105MR-AH012-04P-C1.0-000	TCC-105MR-AH012-04P-R1.0-000
	3	TCC-105MR-AH012-04P-C3.0-000	TCC-105MR-AH012-04P-R3.0-000
	5	TCC-105MR-AH012-04P-C5.0-000	TCC-105MR-AH012-04P-R5.0-000

芯线颜色和顺序 Core wire color and sequence

	Pin 位	
Pin1	1. Brown	1. Brown
Pin2	/	2. White
Pin3	3. Blue	3. Blue
Pin4	4. Black	4. Black

Web: www.tielee.com

TEL: +86-574-6347-9600, 6389-6436

Mail: sale@china-tianli.cn

地址: 中国浙江省宁波杭州湾新区庵东工业园区纬三路138号

ADD: 138, Weisan Rd., Andong Development Zone, Hangzhou Bay Area, Ningbo, Zhejiang, China